



Curved Microphone Kit

STS-K035-B / STS-K035-G-RH

Our speech transfer systems provide assistance for clear communication where normal speech is impaired by use of glass, a security screen or other similar barriers.

There is also a hearing loop facility included with this system which provides additional assistance for hearing aid wearers.

This kit includes our microphone and speaker unit in a curved arrangement, which can be curved to the left or the right, to provide you with the perfect set up.

Components

- Duplex amplifier
- Curved microphone and speaker unit
- Free-standing staff microphone
- Hearing loop aerial

Physical Data (boxed)

Dimensions	Height - 300mm (11.81") Width - 310mm (12.2") Depth - 160mm (6.3")
Weight	2.6kg (5.7lbs)
Construction	Metalwork - Mild Steel Driver - ABS Plastic
Finish	Powder Coated
	 Black Textured BM309E  Grey Leatherette BS 00 A0 5

Applications

For use in any situation where one to one communication takes place at a counter, booth or desk, such as in:

- Banks
- Post offices
- Theatres
- Information Centres
- Airports

Standards

- CE, ROHS and WEEE compliant
- BS EN 60118-4, in correct installations
- Designed to meet IP50
- Designed to meet IP54 (customer side only)

Talk to us now:
 +44 (0) 1732 223900 (UK & ROW)
 +1 616 392 3400 (US & Canada)
www.contacta.co.uk



Physical and Technical Data (Individual Parts)

Components	Physical Data	Technical Data
Amplifier	Dimensions: Height - 116mm (4.57") Width - 115mm (4.53") Depth - 40mm (1.57") Weight: 100g (0.22lbs) Construction: ABS Plastic Construction Housing Finish: Matt Black, Fine Texture	Supply Voltage: 12-14 VDC
		Quiescent current: 100mA typical
		Operating current: 2A typical on speech peaks
		Power switch: Push on - push off (tact switch under membrane)
		Microphones: Electret, supply 5V via 2.2K load resistor
		Speaker output power: RMS: 2.5W / 8 Ω 4.4W / 4 Ω
		Loop drive compliance: Constant current, bounded by 4V RMS & 3A RMS
		Total harmonic distortion: <5% (loop and speakers)
Staff Unit	Dimensions: Height - 70mm (2.76") Width - 100mm (3.94") Depth - 160mm (6.30") Weight: 0.85kg (1.87lbs) Construction: Mild Steel Finish: Powdercoated Grey Leatherette or Matt Black	RMS: 5W
		Impedance: 4 Ω
		Output: SPL 1W @ 1M 85dB
		Frequency response: 150Hz - 10300Hz