

The C 1020-USB is a cardioid condenser microphone, with knuckle joint to allow positioning and mounted on a heavy-duty base. Engineered in high-quality brass with integrated shock mount.



Application	Home markets for use with soft codecs (Zoom, Teams, Google etc)
Type	Condenser (back electret)
Polar Pattern	Cardioid
Frequency Response	50Hz - 20KHz
Sensitivity	-42dB +/- 3dB @1KHz (0 dB = 1 V/Pa , VCC = 5 V, RS = 5.6 KΩ) 1 Pa, A weighted network
S/N Ratio	78dB @ 1KHz
Maximum Sound Pressure Level	136dB at 1KHz 1%THD
Operating Requirements	Win 10 and above Mac OSX and above
Sampling rate	16 Bit @ 48KHz
Termination	1.9M cable terminated with USB-A
Finish	Satin Black
Dimensions	Base Dia 75mm (2.94") Overall height extended 95mm (3.74") Head Dia 20mm (0.79")
Weight	0.08Kg Net, 0.1Kg Gross
Architects and engineer specifications	Rugged wide band cardioid Back electret condenser microphone designed for home markets for use with soft codecs (Zoom, Teams, Google etc). Engineered in high-quality brass. Frequency response 50 – 20 KHz, impedance 0.6KΩ, sensitivity -42dB +/- 3dB @ 1 KHz (0dB = 1 V/Pa). Length: 61mm x 21mm (2.4" x 0.8"). Finish: Satin Black.

