



INTUITIVE AQUACONTROL™ SOFTWARE

he AQM1208 is designed as an advanced, stand-alone zone mixer to be used with external amplification, offering the power & flexibility needed to handle just about any situation. Based on the AquaControl DSP engine first introduced in the mXa1502, the AQM1208 includes a comprehensive library of DSP functions presented in a versatile, yet intuitive UI that doesn't require a college level course to learn. The AQM1208 connects to any browser-enabled device via LAN and Internet from virtually anywhere in the world, allowing convenient remote access for configuration and troubleshooting. The AQM1208's 12 Input by 8 Output configuration meets the requirements for a host of mic mixing, music distribution and other applications, such as noise masking, and provides all the necessary tools to assure everything sounds great and runs smoothly



REMOTE ACCESS ANYWHERE

MIC & MULTI-ZONE READY



Zone Mixer


Intuitive AquaControl™ Software

The AQM1208 on Ashly's next generation AquaControl™ web-server based interface, which means it functions with virtually any networked PC or mobile



Browser-based control from any device


device, any OS. Nothing to install. Plus, it incorporates most of the familiar features found in our legacy Protea DSP software.



Remote Access Anywhere in the World

he AQM1208s remote web access allows integrators to better perform service when customers experience issues.

Logging into the AquaControl environment from their office



rather than sending a truck out to the install site is more convenient and cost-effective and less laborintensive.

Using the Ethernet connection is where things get really amazing. AquaControl provides full remote access to any function via network but can also serve up dedicated remote pages for live mixing or zone control. These can be accessed using any web-enabled device, but the new AquaTouch77" touch panel provides a more elegant on-wall solution for users demanding convenient remote access



The AquaTouch7 Remote is the perfect compliment to AquaControl products

Mic and Multi-Zone Ready

he AQM1208 is equipped to handle a range of applications, from background music distribution to paging, noise-masking a mixing. And



the AQM1208 doesn't come up short when it comes to microphone mixing. 12 fully-featured Mic Inputs with Class A preamps & Phantom Power switchable on each channel, plus useful features such as Auto-Mixing and Priority Ducking make it ideally suited for HoW, Theaters, Conferences, Courtrooms and School Auditoriums.





PRELIMINARY

AQM1208 SPECIFICATIONS	
Number of Input Channels Number of Output Channels Distortion (SMPTE, typical) Distortion (THD-N, typical) Channel Separation	12 (12 Balanced Mic/Line, + 4 Unbalanced Summed RCA Line on 9-12)
Number of Output Channels	8 Balanced Line
Distortion (SMPTE, typical)	<0.5%
Distortion (THD-N, typical)	<0.5% (8 Ohms, 10dB below rated power, 20Hz-20kHz)
Channel Separation	-75dB (dB from full output, 1kHz)
Signal-to-Noise	>110dB (20Hz-20kHz)
Frequency Response	20Hz-20kHz, ±0.05dB
Balanced Input Connector	Euroblock 3.5mm
Input Impedance	10k Ohms
Maximum Input Level	+21dBu
Nominal Voltage Input	100 - 240VAC
Operating Range	70 - 270VAC
AC Mains Line Cord Connector	Detachable Nema 5-15 for USA
Control Network	RJ-45 connector, 1GB Ethernet
Line Output Connector	Balanced Euroblock 3.5mm
Line Output Maximum Level	+21dBu
Remote DC Level Control	Euroblock 3.5mm - Gnd, CV, V+ per input
Unit Dimensions	19"W x 1.75"H x 14.54"D (483mm x 45mm x 369mm)
Dimensions	25.2"W x 2.5"H x 19.5"D / 641mm x 64mm x 495mm
Weight	8.8lbs (4 kg)

1) Note:



AQM 1208
ARCHITECT &
ENGINEERING
SPECIFICATIONS
in .txt format are available in
the DOWNLOADS section of
https://grco.de/be40Lq



Ashly Audio, Inc. • 847 Holt Road • Webster, NY USA • US toll-free +1.585.872.0010 Fax +1.585.872.0739 • Sales@Ashly.com

©2019-2023 Ashly Audio A Division of JAM Industries USA, LLC. All Rights Reserved. Ashly is a registered trademark. Any other trademarks are property of their respective holders.

All Specifications are subject to change.

